




Canes



-  Interior LED luminaire, white powder varnished with highly polished aluminium louvre.
-  Highly polished aluminium anti-glare louvre, with UGR<19. Excellent lighting characteristics with high specific power.
-  Surfaced mounting on ceiling or suspended on wires.

Application

Receptions, offices, partitioned spaces, corridors, computer workspaces, classrooms

Characteristics

Power supply

SD 93–265 V_{AC}, 50–60 Hz, 176–250 V_{DC}

ED 230 V_{AC} ±10 %, 50 Hz

MTBF control gear at 25°C

65 000 h

Luminous flux maintenance at 25°C

>60 000 h (L80B20)



Colour stability 3 SDCM

Mounting surfaced ceiling or suspended

Body steel sheet with white powder varnishing, white colour, RAL 9003


Standard EN 60598-1, EN 60598-2-1, EN 60598-2-22 (fundamental requirements), EN 62471 (photobiological hazard)

IP20 IK05 960° +40°C -20°C UGR<19




| Version | Dimensions mm | | |
|---------|---------------|-----|----|
| | L | B | H |
| 2x 36 W | 934 | 225 | 45 |
| 2x 58 W | 934 | 225 | 45 |

CANES




| | Order Code | Description | Power W | Colour temp. K | CRI | LED flux lm lm (Tj=25°C) | Luminaire flux lm | Brightness efficiency lm/W | Weight kg | Packaging Single/Multi pack | |
|-------------|---|-------------------------|---------|----------------|-----|-----------------------------|-------------------|----------------------------|-----------|-----------------------------|--------------------|
| SD | A39-10148CSD | CANES LED 2x36 SD 4000K | 36 | 4000 | >80 | 4800 | 4000 | 111 | 2.8 | 1 | AUTO-DIMMER |
| | A39-10149CSD | CANES LED 2x58 SD 4000K | 47 | 4000 | >80 | 6160 | 5100 | 109 | 2.8 | 1 | |
| ED | A39-10148C | CANES LED 2x36 4000K | 39 | 4000 | >80 | 5640 | 4700 | 120 | 2.8 | 1 | ON / OFF |
| | A39-10149C | CANES LED 2x58 4000K | 52 | 4000 | >80 | 7200 | 6000 | 115 | 2.8 | 1 | |
| DALI | INTERFACING WITH ACCESSORY TO BE ORDERED SEPARATELY: It is possible to create DALI luminaires by integrating the version SD with the accessory DALI Module – Order Code 15024 Example: Order Code A39-10148CSD + 15024 = Luminaire in the DALI version | | | | | | | | | | DALI |

ACCESSORIES – supplied



SMART DIMMER LIGHT SENSOR

Order Code **15039**




ACCESSORIES – to be ordered separately

WIRE PENDANT WITHOUT POWER CABLE (120 cm)
Order Code **99-080/120/ES**

WIRE PENDANT WITH 3× 1.5 mm² POWER CABLE (120 cm)
Order Code **90-081/120/ES**



WIRE PENDANT WITH 5× 1.5 mm² POWER CABLE (120 cm)
Order Code **90-082/120/ES**


BUILDING AUTOMATION – to be ordered separately



LOGICA SD LGFM CONTROL UNIT


Order Code **21102**







BUILDING AUTOMATION RADIO TRANSMITTER

Order Code **20104**






DALI MODULE **1÷10V MODULE**


Order Code **15024** Order Code **15034**






BUILDING AUTOMATION RADIO MODULE

Order Code **15022**



LED INVERTER EMERGENCY LUMINAIRE – to be ordered separately



INVERTER PLUG&LIGHT SE/SA 1-3h 20-60V

Order Code **19358** (1 h)
Order Code **19359** (3 h)

