

Lunako LED Round, Square

Ceiling and wall LED luminaires



Material:

- body: polycarbonate
- color: white
- diffuser: polycarbonate


Protection degree: IP 54

Power supply: 230 V / 50 Hz


Control gear: LED driver

Mounting: ceiling or wall


Application: hallways and stairways, common and waiting rooms




Lunako LED Round 18W




Lunako LED Round 24W




Lunako LED Round 36W



Lunako LED Square 18W



Lunako LED Square 24W



Lunako LED Square 36W

Lunako LED Round:

Code	Power W	Lum. flux. (lm)	lm/W	Color temp. K	Ra	Dimensions (mm)	Kg
A44-10140BM	18	1 620	90	3 000	80	278 x 49	0.9
A44-10140CM	18	1 700	94	4 000	80	278 x 49	0.9
A44-10160BM	24	2 160	90	3 000	80	327 x 49	1.1
A44-10160CM	24	2 280	95	4 000	80	327 x 49	1.1
A44-10210CM	36	3 600	100	4 000	80	327 x 52	1.1

Lunako LED Square:

Code	Power W	Lum. flux. (lm)	lm/W	Color temp. K	Ra	Dimensions (mm)	Kg
A44-10150CM	18	1 700	94	4 000	80	278 x 278 x 49	0.9
A44-10190CM	24	2 280	95	4 000	80	327 x 327 x 49	1.1
A44-10230CM	36	3 600	100	4 000	80	327 x 327 x 52	1.1