

FH-L Emergenza

PRO/RIF 200W REG 4K TR3H NH

Beghelli Code: **40864TR3**

Beghelli

SYSTEM:RD - TR



Description: Lighting

EAN:

ELECTRICAL AND LIGHTING TECHNICAL CHARACTERISTIC

SUPPLY VOLTAGE TYPE: AC
NOMINAL VOLTAGE AC: 230 V
VOLTAGE SUPPLY RANGE AC: 198 V+265 V
FREQUENCY SUPPLY RANGE: 50 Hz+60 Hz
POWER FACTOR (Cos fi): 0.98
ABSORBED POWER: 203 / 172 / 143 / 114 W
EMERGENCY DIAGNOSTIC TYPE: TR
DURATION: 3 h
FLUX NM: 550 lm
FLUX: 27878 / 24754 / 21497 / 17769 lm
EFFICIENCY: 138 / 144 / 150 / 156 lm/W
BATTERY TYPE: NiMH
BATTERY: NiMH 7.2V 1.5Ah
REST MODE: y
RECHARGING TIME: 24 h
Ta: 0 °C+40 °C
INSULATION CLASS: I
CRI: >80
CCT: 4000 K
COLOR CONSISTENCY (SDCM): SDCM3
LUMINOUS FLUX MAINTENANCE L80/B20: 60000 h
OPTIC NAME: SYMMETRIC / ASYMMETRIC
OPTIC EFFICIENCY: 100% / 97%
LED NUMBER: 576
DRIVER TYPE: For constant current LED
DRIVER LIFE MTBF: 50000 h
DIMMER TYPE: RD
INRUSH: 34 A,0.2 ms
QUANTITY BREAKER: B16 18
QUANTITY BREAKER: C16 18
PHOTOBIOLOGICAL RISK: RG0

MOUNTING AND APPLICATIONS

ENVIRONMENT: Indoor/Outdoor

MECHANICAL CHARACTERISTICS

Dimension: Height: 121 mm Length: 434 mm Width: 438 mm
PRODUCT WEIGHT: 8.8 kg
BODY MATERIAL: Die-cast aluminium **COLOUR** Grey
COVER / DIFFUSER MATERIAL: Tempered microprismatic glass
REFLECTOR MATERIAL: Specular Aluminium **COLOUR** Metal
WIND SURFACED EXPOSED: 1755 cm²
PROTECTION DEGREE: IP66
MECHANICAL IMPACTS PROTECTION DEGREE: IK09
GLOW WIRE: 960° - 30s.
QUANTITY PER BOX SINGLE/MULTIPLE/DELIVERY: 1//1

CERTIFICATES AND STANDARDS

STANDARDS: CEI EN 60598-2-5, CEI EN 60598-1, EN 62471, 2009/125/CE, 874/2012/CE, 2014/30/EU, 2014/35/EU


PRO/RIF 200W REG 4K TR3H NH

SYSTEM:RD - TR


Beghelli Code: **40864TR3**



ASYMMETRIC (97%)



SYMMETRIC



Accessories to be order separately



12658

GRIGLIA DI PROTEZIONE MF



12659

STAFFA FISSAGGIO BARRA
ELET MF



12661

TESTA PALO 2X 60-76



12662

TESTA PALO 4X 60-76



12663

CAVO SOSPENSIONE
RIFLETTORE



12664

STAFFA FISSAGGIO PLAFONE