



X-Six LED - CCT

X-SIX DWL LED CCT REG 18W

Versatile appliance designed for both recessed and ceiling installation with a quick bayonet bracket. Equipped with CCT function with 3 different color temperatures that can be adjusted using the selector located on the back of the unit. All accessories are included in the packaging.




Order code 71062

EAN 8002219754875

Technical specifications

Absorbed Power	18 W
Supply voltage type	AC
Nominal voltage (AC)	230 Vac
Ambient temperature (min)	-20 °C
Ambient temperature (max)	40 °C
Insulation class	II
CCT light tone	3000 K, 4000 K, 6000 K
CCT (max)	6000 K
CCT (min)	3000 K
LED number	96
Beam angle	120 °
Colour consistency	SDCM3
CRI color rendering	>80
Diameter	225 mm
Ballast	For constant current LED
Efficiency	80 lm/W
Frequency (max)	60 Hz
Frequency (min)	50 Hz
Power factor	0.55
Glow wire strength	550 °C - 30s.
Luminaire flux	1440 lm
Luminous flux L80B20	50000 h
Mounting	Ceiling, Recessed
Voltage supply range (max)	253 V
Voltage supply range (min)	207 V



Foro di ingresso Ø 65-210 mm


Installation and applications

Environment	Offices
Application	Offices, Condos, Hotels, Malls, Shops

Mechanical specifications

Height	20 mm
Weight	0.4 Kg
Colour housing	White
Protection grade IP	IP20
Protection grade IK	IK05

Certifications and norms



UK SI 2021 No. 1095, EN 62471:2008, EN
IEC 60598-1:2021, EN 60598-2-2:2012, EN
IEC 63000:2018, EN 62493:2010, EN
61000-3-3:2013, REG. 2019/2020(EU), EN
IEC 55015:2019 + A11:2020, EN IEC 61000-
3-2 :2019