



Stagna Easy LED

STAGNA EASY CCT IP65 120CM 40W

Compact CCT LED ceiling light with IP65 waterproof rating, with diffusing opaline screen made of polycarbonate. Calibrated heads attached to the central body and internal terminal block for quick installation.

Order code 75461

EAN 8002219895486

Technical specifications

Absorbed Power	40 W
Supply voltage type	AC
Nominal voltage (AC)	230 Vac
Ambient temperature (min)	-20 °C
Ambient temperature (max)	40 °C
Insulation class	II
CCT light tone	3000 K, 4000 K, 6500 K
LED number	144
Colour consistency	SDCM2
CRI color rendering	>80
Ballast	For constant current LED
Efficiency	110 lm/W
Equivalent power	2x36w
Frequency (max)	60 Hz
Frequency (min)	50 Hz
Power factor	0.9
Glow wire strength	550 °C - 30s.
MTBF driver	35000 h
Luminaire flux	4400 lm
Luminous flux L70B50	50000 h
Mounting	Ceiling
Voltage supply range (max)	240 V
Voltage supply range (min)	220 V

Installation and applications

Environment	Secondary Areas
Application	Offices, Production, Warehouses

Mechanical specifications

Height	74 mm
Length	1200 mm
Width	61 mm
Weight	1.5 Kg
Colour housing	Light Grey
Protection grade IP	IP65
Protection grade IK	IK08

Certifications and norms



UK SI 2021 No. 1095, EN 62471:2008, EN
IEC 60598-1:2021, EN 60598-2-1:1989, EN
IEC 63000:2018, EN 62493:2010, EN
61000-3-3:2013, REG. 2019/2020(EU), EN
IEC 55015:2019 + A11:2020, EN IEC 61000-
3-2 :2019

Accessories



201954000

KIT 2 GANCI SOSPEN ST EASY
LED