



X-Six LED - CCT

X-SIX DWL LED CCT REG 24W



Versatile appliance designed for both recessed and ceiling installation with a quick bayonet bracket. Equipped with CCT function with 3 different color temperatures that can be adjusted using the selector located on the back of the unit. All accessories are included in the packaging.

Order code 71063

EAN 8002219754882

Technical specifications

| | |
|----------------------------|---------------------------------|
| Absorbed Power | 24 W |
| Supply voltage type | AC |
| Nominal voltage (AC) | 230 Vac |
| Ambient temperature (min) | -20 °C |
| Ambient temperature (max) | 40 °C |
| Insulation class | II |
| CCT light tone | 3000 K, 4000 K, 6000 K |
| CCT (max) | 6000 K |
| CCT (min) | 3000 K |
| LED number | 200 |
| Beam angle | 120 ° |
| Colour consistency | SDCM3 |
| CRI color rendering | >80 |
| Diameter | 330 mm |
| Ballast | For constant current LED |
| Efficiency | 80 lm/W |
| Frequency (max) | 60 Hz |
| Frequency (min) | 50 Hz |
| Power factor | 0.55 |
| Glow wire strength | 550 °C - 30s. |
| Luminaire flux | 1920 lm |
| Luminous flux L80B20 | 50000 h |
| Mounting | Ceiling, Recessed |
| Voltage supply range (max) | 253 V |
| Voltage supply range (min) | 207 V |



Installation and applications

| | |
|-------------|--|
| Environment | Offices |
| Application | Offices, Condos, Commercial Areas, Hotels, Malls, Shops |

Mechanical specifications

| | |
|---------------------|---------------|
| Height | 20 mm |
| Weight | 0.8 Kg |
| Colour housing | White |
| Protection grade IP | IP20 |
| Protection grade IK | IK05 |

Certifications and norms

UK SI 2021 No. 1095, EN 62471:2008, EN IEC 60598-1:2021, EN 60598-2-2:2012, EN IEC 63000:2018, EN 62493:2010, EN 61000-3-3:2013, REG. 2019/2020(EU), EN IEC 55015:2019 + A11:2020, EN IEC 61000-3-2 :2019

