



X-Six LED - CCT

X-SIX LED CCT REG MULTIPOWER S

Order code 71064

EAN 8002219887436

Technical specifications

Absorbed Power	9 W, 12 W, 18 W
Supply voltage type	AC
Nominal voltage (AC)	230 Vac
Ambient temperature (min)	-20 °C
Ambient temperature (max)	40 °C
Insulation class	II
CCT light tone	3000 K, 4000 K, 6000 K
CCT (max)	6000 K
CCT (min)	3000 K
LED number	114
Beam angle	120 °
Colour consistency	SDCM3
CRI color rendering	>80
Diameter	225 mm
Ballast	For constant current LED
Efficiency	90 lm/W
Frequency (max)	60 Hz
Frequency (min)	50 Hz
Power factor	0.55
Glow wire strength	550 °C - 30s.
MTBF driver	30000 h
Luminaire flux	810 lm, 1080 lm, 1620 lm
Mounting	-, Ceiling, Recessed
Voltage supply range (max)	253 V
Voltage supply range (min)	207 V



Installation and applications

Environment	Offices
Application	Offices, Condos, Commercial Areas, Hotels, Malls, Shops

Mechanical specifications

Height	20 mm
Weight	0.5 Kg
Colour housing	White
Protection grade IP	IP20
Protection grade IK	IK05

Certifications and norms

UK SI 2021 No. 1095, EN IEC 55015:2019 + A11:2020, EN IEC 61000-3-2 :2019, EN 61547:2009, EN 62471:2008, EN IEC 60598-1:2021, EN 60598-2-2:2012, EN IEC 63000:2018, EN 62493:2010, EN 61000-3-3:2013

